



Prm 260

Nominal Power Ratings, PRM 260 Marine Gearbox

Ratios	Pleasure		Light Commercial		Heavy Commercial	
	BHP	kW	BHP	kW	BHP	kW
1.96:1	3.65	2.72	3.36	2.51	3.08	2.31
2.94:1	3.65	2.72	3.36	2.51	3.08	2.31

Maximum operating speeds:
4500 rev/min intermittent, 4000 rev/min continuous

Approximate Weight & Oil Capacity

Gearbox	Approximate dry weight	Oil capacity
PRM260D	48kg (106lb)	1.5 litres (2.64 pints)
PRM260C	63kg (138lb)	1.70 litres (3.0 pints)

excluding adaptor, drive coupling and oil cooler.
plus the amount require to fill the cooling circuit

Flexible Input Couplings for PRM260

Part Number	Outside Diameter		No.	Mounting Hole Pattern				Remarks
	in	mm		Diameter		Pitch Circle Dia.		
				in	mm	in	mm	
MT1224	9.50	241.3	8	0.344	8.74	8.750	222.3	SAE 7 ½ in
MT1222	12.375	314.3	6	Multi Punched - Dimensions on application				
			8	0.375	9.53	11.625	295.3	SAE 10 in
MT1162	13.875	352.4	8	0.433	10.99	13.125	333.4	SAE 11 ½ in
MT1213	14.25	362.0	6	0.320	8.13	11.625	295.3	Perkins 4-236
			6	Multi Punched - Dimensions on application				
MT4911	13.875	352.4	8	0.433	10.99	13.125	333.4	SAE 11 ½ in High Deflection
MT4912	14.25	362.0	6	0.320	8.13	11.625	295.3	Perkins 4-236
			6	Multi Punched - Dimensions on application				High Deflection
MT4913	12.375	314.3	6	Multi Punched - Dimensions on				



			application					
			8	0.375	9.53	11.625	295.3	SAE 10 in High Deflection
MT4914	9.50	241.3	8	0.344	8.74	8.750	222.3	SAE 7 ½ in High Deflection
MT1468	14.25	362.0	6	Multi Punched - Dimensions on application				(For 260C)

Adaptor Flanges For PRM260

Part Number	Description	Weight	
		kg.	lb.
MT8074S/A	SAE 2 Adaptor Flange	13.0	28.7
MT854S/A	SAE 3 Adaptor Flange	11.0	24.3
MT1210S/A	SAE 4 Adaptor Flange	10.0	22.0
MT1209S/A	SAE 5 Adaptor Flange	7.0	15.4
MT1426S/A	B/W (Velvet Drive) adaptor Flange	4.3	9.5

Other Accessories For PRM260

Part Number	Description	Weight	
		kg.	lb.
MT913S/A	Oil cooler	1.2	2.6
MT915	Oil pipes (pair)	0.5	1.1
MT784	Oil cooler mounting bracket	0.2	0.4
MT771	Tailshaft half coupling (pilot bored)	2.5	5.5
MT1104	Tailshaft flexible coupling	1.5	3.3
MT0214	Neutral safety start switch	0.04	0.1
MT4733	Oil pressure gauge (direct mounting)	0.1	0.2
MT4990	Trolling Valve Assembly 12V	9.5	20.9
MT4991	Trolling Valve Assembly 24V	9.5	20.9