



## Rating

Model	Shaft Arrangement	Ratio Ahead/Astern	Max Input Speed rev/min		Nominal Power Ratings Per 100 rev/min					
			Continuous	Intermittent	Pleasure		Light Commercial		Heavy Commercial	
					kW	BHP	kW	BHP	kW	BHP
<a href="#">PRM80</a>	Offset	2.04:1	5000	-	0.84	1.12	0.55	0.74	-	-
		2.50:1	5000	-	0.73	0.98	0.48	0.65	-	-
<a href="#">PRM120</a>	Offset	2.04:1	5000	-	1.25	1.67	0.68	0.91	-	-
		2.50:1	5000	-	1.00	1.34	0.68	0.91	-	-
		2.94:1	5000	-	0.83	1.11	0.58	0.77	-	-
<a href="#">PRM150</a>	Offset	1.53:1	4500	5000	1.6	2.1	1.1	1.5	-	-
		2.09:1	4500	5000	1.6	2.1	1.1	1.5	-	-
		2.82:1	4500	5000	1.6	2.1	1.1	1.5	-	-
<a href="#">PRM260</a>	Offset & In-line	1.963:1	4000	4500	2.72	3.65	2.51	3.36	2.31	3.08
		2.941:1	4000	4500	2.72	3.65	2.51	3.36	2.31	3.08
<a href="#">PRM500</a>	Offset	1.459:1	4000	4500	4.76	6.38	4.62	6.19	4.40	5.90
		1.935:1	4000	4500	4.76	6.38	4.62	6.19	4.40	5.90
		2.565:1	4000	4500	4.62	6.19	4.40	5.90	4.40	5.90
		2.904:1	4000	4500	4.62	6.19	4.40	5.90	4.40	5.90
<a href="#">PRM750</a>	8° Down Angle	1.09:1	4000	4500	7.17	9.62	5.68	7.62	5.39	7.23
		1.459:1	4000	4500	7.17	9.62	5.68	7.62	5.39	7.23
		1.935:1	4000	4500	7.07	9.48	5.68	7.62	5.39	7.23
		2.565:1	4000	4500	7.07	9.48	5.68	7.62	5.39	7.23
		2.904:1	4000	4500	5.96	8.00	5.60	7.51	5.24	7.02



<a href="#">PRM750</a>	Offset & In-line  3.95:1 In-Line Not Available	1.09:1	4000	4500	7.85	10.5 2	6.07	8.13	5.86	7.85
		1.459:1	4000	4500	7.85	10.5 2	6.07	8.13	5.86	7.85
		1.935:1	4000	4500	7.07	9.46	5.86	7.85	5.55	7.43
		2.565:1	4000	4500	7.07	9.46	5.86	7.85	5.55	7.43
		2.904:1	4000	4500	5.96	8.00	5.60	7.50	5.24	7.02
		3.952:1	4000	4500	5.96	8.00	5.60	7.50	5.24	7.02
<a href="#">PRM1000D</a>	Offset Only	1.528:1	3000	3500	10.4 7	14.0 4	7.75	10.39	7.33	9.82
		2.033:1	3000	3500	9.43	12.6 4	7.44	9.96	7.02	9.40
		2.857:1	3000	3500	8.58	11.5 0	7.44	9.96	7.02	9.40
		4.000:1	3000	3500	8.58	11.5 0	7.44	9.96	7.02	9.40
<a href="#">PRM1000A</a>	10° Down Angle	1.528:1	3000	3500	9.66	12.9 5	7.10	9.52	6.67	8.95
		2.033:1	3000	3500	9.43	12.6 4	7.10	9.52	6.67	8.95
		2.857:1	3000	3500	8.58	11.5 0	7.10	9.52	6.67	8.95
<a href="#">PRM1500D</a>	Offset	3.12:1	2500	3000	15.7 0	21.0 6	14.65	19.65	13.63	18.28
		3.88:1	2500	3000	15.7 0	21.0 6	14.65	19.65	13.63	18.28
		4.50:1	2500	3000	15.7 0	21.0 6	14.65	19.65	13.63	18.28
		4.90:1	2500	3000	13.6	18.2	12.58	16.87	11.53	15.46



					3	8				
<a href="#">PRM1500S</a>	Offset	1.22:1, 1.56:1	2500	3000	15.7 0	21.0 6	14.65	19.65	13.63	18.28
		1.94:1, 2.25:1	2500	3000	15.7 0	21.0 6	14.65	19.65	13.63	18.28
		2.45:1	2500	3000	15.7 0	21.0 6	14.65	19.65	13.63	18.28
		3.0:1	2500	3000	14.1 2	18.9 3	13.07	17.52	11.76	15.77
<a href="#">PRM1750D</a>	Offset	3.12:1	2500	3000	24.5 8	18.3 3	22.85	17.04	21.13	15.76
		3.88:1	2500	3000	24.5 8	18.3 3	22.85	17.04	21.13	15.76
		4.50:1	2500	3000	24.5 8	18.3 3	22.85	17.04	21.13	15.76
		4.90:1	2500	3000	22.4 8	16.7 6	20.89	15.58	19.32	14.41
<a href="#">PRM1750S</a>	Offset	1.22:1, 1.56:1	2500	3000	24.5 8	18.3 3	22.85	17.04	21.13	15.76
		1.94:1, 2.25:1	2500	3000	24.5 8	18.3 3	22.85	17.04	21.13	15.76
		2.45:1	2500	3000	24.5 8	18.3 3	22.85	17.04	21.13	15.76
		3.0:1	2500	3000	24.5 8	18.3 3	22.85	17.04	21.13	15.76

If you can not find your current model in this list please refer to the information on [older models](#) no longer in production.